

Hydraulic Power Packs

HA 1-ES and HA 3



HA 1-ES and HA 3

Ref.No. 31070 & 33340 / 32530



Advantages

Leaders when it comes to switchgear manufacturing. Novopress hydraulic power packs are operating at a low pressure of 150 bar (2,200 psi) over a wide range of applications. This design combines the clear advantages of increased safety and long service life for the power pack and its attached devices. In addition, these hydraulic power packs area are a byword for the high quality associated with all Novopress products.

- ▶ durable 150 bar (2,200 psi) low pressure
- ▶ gear pump with high flow rate
- ▶ 3-Layer safety switch
- ▶ suitable for „S1 continuous operation“ (only HA 3)

	HA 1-ES	HA 3
Drive	E-Motor, 230 V- 800 W, 4 A	E-Motor, 230 V- 800 W, 4 A
Weight	18 kg	26 kg
Height	470 mm	550 mm
Width	280 mm	270 mm
Oil capacity	3.5 l	5.5 l
Operation	25 %, 100 s	S 1
Safety	IP 44	IP 44
Connection cable	5 m	5 m
Hydr. hose	2.5 m	2.5 m
Operating pressure	150 bar	150 bar
Flow rate	4.5 l/min	3.5 l/min

We reserve the right to make technical modifications.

Hydraulic Power Packs

HA 1-ES and HA 3




Accessories



Multi-way valve MV 3 Ref.No. 3240

The Multi-way valve MV 3 allows to operate up to three HSBL units* with only one power pack without having to change the hydraulic connection. By simply switching, you can select the desired processing of your current busbar. This enables a fast and uncomplicated work.

*for safety reasons always only the connected device



We reserve the right to make technical modifications.